

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 April 2005 (07.04.2005)

PCT

(10) International Publication Number
WO 2005/029975 A1

(51) International Patent Classification⁷: **A23L 1/00**,
A21D 13/08, A23L 1/00

(21) International Application Number:
PCT/NL2004/000271

(22) International Filing Date: 23 April 2004 (23.04.2004)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:
1023257 24 April 2003 (24.04.2003) NL

(71) Applicant (for all designated States except US): **NED-
ERLANDSE ORGANISATIE VOOR TOEGEPAST-
NATUURWE- TENSCHAPPELIJK ONDERZOEK
TNO** [NL/NL]; Schoemakersstraat 97, NL-2628 VK Delft
(NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **DON, Johannes,
Andreas, Clyde** [NL/NL]; Generaal Foulkesweg 14,
NL-6703 BR Wageningen (NL). **NOORT, Martijn**,

Willem-Jan [NL/NL]; Emmastraat 39, NL-1213 AJ
Hilversum (NL). **PLIJTER-SCHUDDEMAT, Johanna**
[NL/NL]; Oranjestraat 5, NL-3921 BA Elst (NL). **VAN
SON, Matheus, Wilhelmus, Louis, Jozef** [NL/NL];
Strawinskystraat 44, NL-3438 XP Nieuwegein (NL).
PLIJTER, Johannes, Jozef [NL/NL]; Oranjestraat 5,
NL-3921 BA Elst (NL).


(74) Agent: **WINCKELS, J., H., F.**; Verenigde, Johan de Wit-
tlaan 7, NL-2517 JR Den Haag (NL).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: **MOISTURE-BARRIER COATING LAYER FOR FOODS**



(57) Abstract: The invention relates to a moisture -barrier coating layer for foods, to a method for applying such a coating layer to a food, and to a food provided with such a coating layer. According to the invention, it has been found that transport of water between components with a different moisture content in a composite food can be prevented, at least inhibited, by using a coating layer between the two components, which coating layer is based on an acetoglyceride or mixture of acetoglycerides in which a particular, minimum amount of shortchain fatty acids is present.



Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

Moisture-barrier coating layer for foods

The invention relates to a moisture-barrier coating layer for foods, to a method for applying such a coating layer to a food and to a food provided with such a coating layer.

The preservability of foods is, in addition to being enhanced by factors preventing decay, enhanced by measures reducing the diffusion of moisture through and/or from the product. For instance, a moisture impermeable package around a loaf of bread prevents it from dehydrating rapidly.

The use of a coating layer having moisture-barrier properties is particularly advantageous for composite foods in which the water content in the various components is different and may not alter significantly during storage. A moisture-barrier coating layer in or on a food must purely consist of edible ingredients and be edible as a whole as well.

To realize this, a number of products, typically based on fat (i.e. chocolate and mayonnaise), are used to keep different components in composite foods having different moisture contents separated from each other. However, in practice, the moisture resistance of these so-called moisture-barriers is found to be too low, of too limited applicability or too short in duration. A moisture-barrier protective layer consisting of, for instance, chocolate can be affected by temperature and, moreover, has a highly characteristic flavour which is not always desired. Mayonnaise can penetrate into the surrounding food or be incorporated therein, thereby causing, over time, the moisture-barrier protective layer to become thinner. For that reason, the moisture-barrier action and applicability of a number of existing, edible moisture-barriers are limited and improvement is desired.

Alternative solutions are based on a reduction of the difference between the water activities (A_ws) of the components between which transport of moisture is to be prevented. An example of such a solution consists in the

reduction of the A_w of the stuffing of cake which is in contact with a moist component such as custard. In order to delay the transport of water, the stuffing is made to be extremely sweet which, because of the flavour, is often undesirable, or a very sweet jam is provided between the yellow pastry cream and a bottom of, in this case, a flan.

Much research in the field of edible moisture-barriers, inter alia for coating tablets, has been carried out by the pharmaceutical industry. For instance, British patent application 756082 describes that the moisture sensibility of tablets can be reduced by mixing the moisture-sensitive powders with a solution of a prolamin in alcohol and then to process this into tablets.

Shellac, often in combination with hydroxypropyl cellulose, is also an often used biopolymer in the application of a moisture-barrier coating on foods (see, inter alia, US 4,820,533). The combination of shellac with prolamin is used for this purpose as well (EP 0 090 559).

In the international patent application 95/23520, an ice cream composition is described in which sugar particles are present, encapsulated in a layer of butterfat. The sugar particles are very small ($< 2000 \mu\text{m}$). Owing to the layer of butterfat, the sugar is prevented from dissolving in the ice cream and causing the ice cream to have a lower melting point. The eventual product has the same flavour and mouthfeel properties as normal ice cream but can be kept in frozen condition easier.

There is a strong need for edible coating layers with a better moisture-barrier action, with a longer life span, with broader applicability, with a higher temperature stability and with a greater elasticity. To a large extent, this need is motivated by the growth of the market of composite foods, including convenience food. In such foods, moisture-containing ingredients are combined with dry ingredients. The occurrence of moisture migration or moisture diffusion through the food causes a rapid and considerable reduction of the flavour and the texture of the food and in particular of the dry ingredients.

According to the invention, it has now been found that water transport between components with a different moisture content in a composite food can be prevented, at least inhibited by using a coating layer between the two components, which coating layer is based on an acetoglyceride of a mixture of acetyoglycerides in which a particular, minimum amount of short-chain fatty acids is present.

Such a coating layer is more effective than coating layers based on heterogeneous fats, which is particularly surprising since it is known that, in general, in this field of application, acetoglycerides function less well than heterogeneous fats. In this connection, reference can be made to, for instance, international patent application 97/15198.

Hence, in a first aspect, the invention relates to a coating layer for inhibiting water transport between components having a different moisture content in a composite food, which coating layer comprises an acetoglyceride or mixture of acetoglycerides, wherein at least 20%, preferably at least 30% of the fatty acid chains contains less than 10 carbon atoms or has been replaced with a hydroxyl group, which acetoglyceride or mixture of acetoglycerides is solid for at least 40% by weight.

In a second aspect, the invention relates to a composite food comprising components with a different moisture content between which a coating layer has been applied for inhibiting water transport between the components, which coating layer comprises an acetoglyceride or mixture of acetoglycerides in which at least 30 % of the fatty acid chains contains less than 10 carbon atoms or has been replaced with a hydroxyl group.

The invention further relates to a method for preparing a composite food comprising components with a different moisture content, wherein between the components a coating layer is provided, which coating layer comprises a solid acetoglyceride or solid mixture of acetoglycerides in which at least 30% of the fatty acid chains contains less than 10 carbon atoms or has been replaced with a hydroxyl group.

Surprisingly, it has been found that a coating layer according to the invention is capable of preventing water transport between components in a composite food in a highly efficient manner and for a long period of time. Dry biscuits particles coated with a coating layer according to the invention, for instance, can remain dry and crunchy for a very long period of time even when they have been incorporated into a highly aqueous component such as custard or ice cream. In contrast with known, fat-based coating layers for inhibiting water transport in composite foods, a coating layer does not exhibit breakage during storage or through contact with a highly aqueous component of a food.

10 The presence of a coating layer according to the invention has no or hardly any noticeable effect on the flavour experience of a food. The mouthfeel is basically not adversely affected either.

As stated, a coating layer according to the invention comprises a specific acetoglyceride or mixture of acetoglycerides. Preferably, the coating layer consists substantially only of this acetoglyceride or acetoglyceride mixture. According to the invention, acetoglyceride is understood to mean a glycerol esterified with three fatty acids. Specifically, at least 20%, preferably at least 30% of all fatty acids in the acetoglyceride or of all fatty acids in the mixture of acetoglyceride, is short-chained, or has been replaced with a hydroxyl group.

If a mixture of acetoglycerides is used, it is desired that the mixture is homogeneous. This means that the different acetoglycerides are very thoroughly mixed together. Preferably, this condition is stable over time, so that the mixture substantially does not spontaneously separate.

25 The term short-chain fatty acid chain is understood to mean a fatty acid chain containing no more than 10, preferably no more than 8 carbon atoms. Of the 20%, preferably 30% fatty acid chains mentioned, preferably at least half contains less than 4 carbon acids. The remaining fatty acid chains in the acetoglyceride or mixture of acetoglycerides are long-chain fatty acid.

chains, i.e. they contain at least 16, preferably between 16 and 22 carbon atoms.

If a mixture of acetoglycerides is used, preferably, no more than 20% by weight of mono and/or diglycerides are present, calculated on the mixture of acetoglycerides. It is particularly preferred that no single fatty acid chain at all is replaced with a hydroxyl group.

The acetoglyceride or mixture of acetoglycerides which is incorporated into a coating layer according to the invention is solid. This means that under the conditions in which water transport in the eventual food is to be inhibited (the so-called application temperature) the acetoglyceride or mixture of acetoglycerides is solid. Often, the storage and consumption temperatures of the food will then be of importance. In this context, the term solid means that the acetoglyceride or mixture of acetoglycerides is for at least 40%, and preferably substantially entirely, in crystallized condition. For a description of the nature and possible preparation of acetoglycerides, reference is made to the international patent application 94/18290 and US patent 5,380,544. The content of both documents is understood to be incorporated herein by reference.

Optionally, a coating layer according to the invention can also contain suitable additives. Examples of such additives are emulsifiers, sugar, cocoa powder, aromatics, colorants, anti-oxidants and the like. These additives will always be present in small amounts, so that the coating layer consists of the above-described acetoglyceride or mixture of acetoglycerides for at least 95, preferably at least 99 % by weight, calculated on the weight of the coating layer.

For the application of a coating layer according to the invention, first, a composition is prepared of all components desired in the coating layer. As a rule, this will only be the acetoglyceride or mixture of acetoglycerides. This composition is brought into a processible form, for instance by melting or by dissolving, dispersing or emulsifying

suitable solvents are solvents suitable to be used in foods and which can be easily removed through, for instance, evaporation. Specific examples are water and ethanol. When a solvent is used, the solution, dispersion or emulsion of the acetoglyceride or mixture of acetoglycerides will contain between 10 and 99%
5 by weight, preferably between 50 and 90 % by weight of the acetoglyceride or mixture of acetoglycerides, calculated on the weight of the solution, dispersion or emulsion.

The processible (liquid) composition can be applied in a suitable manner to a component which is incorporated into a composite food according
10 to the invention. This can be done by means of coating with the aid of a liquid curtain, in a fluidized bed, through panning, spreading, spraying, spouting, atomizing, immersing, brushing and/or rolling. Preferably, this is done at a temperature above the melting point of the acetoglyceride or mixture of acetoglyceride used. The composition applied to the food is then preferably
15 cured or dried. Curing can be done at a temperature below the crystallization temperature of the acetoglyceride or mixture of acetoglycerides (for instance between 0 and 15°C). Drying can be done at room temperature or at a slightly increased temperature, but preferably at a temperature below the melting temperature of the acetoglyceride or mixture of acetoglycerides. Preferably, the
20 solvent used is substantially completely evaporated from the composition. After curing or evaporation of the solvent, a moisture-barrier, edible coating layer having the above-described properties remains behind on the food.

It is desired that, after having been applied to a component of a food which, as a rule, can also be considered to be a food in itself, the coating layer
25 is not exposed to high temperatures, preferably not to a temperature above the melting temperature of the coating layer. This means that (if necessary) the component should, in advance, be boiled, baked, pasteurized or sterilized or must have undergone a different desired heat treatment.

Depending on the use, a thicker or thinner coating layer will be
30 desired. A minimal thickness of ~50 µm

attainable thickness is a few millimeters. Preferably, the coating layer has a thickness between 50 and 2000 micrometers.

Foods on which or in which the moisture-barrier edible coating layer can preferably be used are composite foods in which the regulation of moisture migration is desired so as to maintain the product quality. Often, the moisture-barrier coating layer will be applied between different layers in the food or between different parts. It is possible to provide moisture-sensitive parts of a food in advance with a moisture-barrier coating layer and, thereupon, incorporate them into the food.

10 Foods onto which or in which a moisture-barrier edible coating layer according to the invention can be applied are, inter alia

- pastry and cake with a stuffing, and flan, pizza, quiche, waffle or pancake;

- bread with a stuffing including sausage roll and almond-paste

15 pastry;

- fruits, chocolate, nuts, muesli, cereals, cornflakes, candy, processed in custard, ice cream, milk, icing, pudding, syrup, yogurt or other liquid or moisture containing products;

- ready-made sandwiches and toast, including pre-packaged bread

20 rolls and sandwiches; and

- stuffed products such as candy bars or muesli-bars.

The invention will presently be elucidated further with reference to the following examples which should not be construed to be limitative.

25 Examples

To compare the moisture-barrier properties of different coating layers, coating layers are applied to an application-model system. Here, a product with a low water activity (A_w) is coated with a coating layer and then exposed to a product with a high A_w . Due to the difference in A_w , water

30 migration will occur in the direction of

decelerated, to a greater or lesser extent, by the presence of the coating layer. The rate at which the A_w of the product, initially having a low A_w , increases, is a measure for the moisture-barrier properties of the coating layer.

The application-model system used consists in a formed cookie, cast
5 in bees wax in the cover of a Petri dish. A liquid composition for the preparation of a coating layer is applied to the surface of the cookie with the aid of a brush. When the layer has cured, the cover is put on the bottom of the Petri dish which is filled with a product with a high A_w . As the bees wax allows virtually no water migration, water can only migrate to the cookie by
10 penetrating the coating layer. By measuring the A_w -value of the cookie as function of time, the moisture-barrier properties of the coating layer are determined.

In the experiment carried out according to the invention, acetoglycerides (Benefat 1H, Danisco Cultor) are provided in the application-
15 model system, they were melted to that end until no solid phase was present any longer (70°C). Thereupon, the temperature was reduced until the desired application temperature was obtained (50°C). With the aid of a brush, the material was applied to the surface of the cookies which, in advance, had been brought to be desired temperature. It was ensured that the temperature of the
20 surface of the cookies was lower than the crystallisation temperature of the material that was applied. The coating layers were applied in two steps. A second amount was applied after the first amount had crystallised. The amount of acetoglyceride provided was 0.062 g/cm³. This yielded a maximum average layer thickness of 0.56 millimetres. As the material gradually
25 penetrates into the cookie, this average layer thickness will, in reality, be lower, depending on the temperature of the coating layer and the surface of the cookie. When mention is made of a maximum average layer thickness, this is understood to mean the layer thickness that would be obtained if the material did not penetrate the cookie.

Thereupon, the Aw-value of the cookie was measured as function of time with an Aqualab CX-3 meter. Here, a circular sample was cut from the cookie in the application-model and stripped of the coating layer. The sample was cut up into little pieces whereupon the Aw-value was measured.

- 5 Thereupon, a comparative experiment was carried out with heterogeneous fat (Frucaps). The results of the measurements are represented in Fig. 1. From Fig. 1 it appears that the results with acetoglycerides are indeed surprisingly better than those with heterogeneous fat (Frucaps).

Claims

1. A coating layer for inhibiting water transport between components with a different moisture content in a composite food, which coating layer comprises an acetoglyceride or mixture of acetoglycerides in which at least 20% of the fatty acid chains contains less than 10 carbon atoms or has been
5 replaced with a hydroxyl group, which acetoglyceride or mixture of acetoglycerides is solid for at least 40% by weight.
2. A coating layer according to claim 1, wherein at least 10% of the fatty acid chains in the acetoglyceride or mixture of acetoglycerides contains less than 4 carbon atoms.
- 10 3. A coating layer according to claim 2, wherein the acetoglyceride or mixture of acetoglycerides contains between 20 and 95% of fatty acid chains having from 2 to 10 carbon atoms and between 5 and 80% of fatty acid chains having from 16 to 22 carbon atoms.
4. A coating layer according to any one of the preceding claims,
15 wherein the mixture of acetoglycerides contains less than 20% mono and/or diglycerides.
5. A composite food comprising components with a different moisture content between which a coating layer according to any one of the preceding claims is applied for inhibiting water transport between the components.
- 20 6. A method for preparing a composite food comprising components with a different moisture content, wherein, between the components, a coating layer according to any one of claims 1 – 5 is applied.
7. A method according to claim 6, wherein at least one of the components is provided with the coating layer through application of a liquid
25 composition comprising the acetoglyceride or mixture of acetoglycerides by means of covering with the aid of a liquid curtain, in a fluidized bed, through

panning, spreading, spraying, spouting, atomizing, immersing, brushing and/or rolling.

8. A method according to claim 7, wherein the liquid composition is obtained by melting the acetoglyceride or mixture thereof.

5 9. A method according to claim 8, wherein the liquid composition is cured after application.

10. A method according to claim 9, wherein the liquid composition is obtained by dissolving or dispersing the acetoglyceride or mixture thereof in a suitable solvent.

10 11. A method according to claim 10, wherein the liquid composition is dried after application.




Fig. 1

INTERNATIONAL SEARCH REPORT

International Application No
PCT/NL2004/000271

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A23L1/00 A21D13/08 A23L1/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A23L A21D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EP0-Internal, PAJ, WPI Data, FSTA

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97/15198 A (UNILEVER NV ; UNILEVER PLC (GB); HEUVEL WILHELMUS M J G (GB); LEWIS ST) 1 May 1997 (1997-05-01) cited in the application claims 1,2 page 7, line 1 - page 10, line 4 page 11, line 12 - page 12, line 9 page 16; example B	1-11
X	US 5 662 953 A (CHRYSAM MICHAEL M ET AL) 2 September 1997 (1997-09-02) column 5, line 25 - column 6, line 34 column 8, line 15 - line 22 column 13, line 5 - line 11 ----- -/-	1-11

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

27 July 2004

Date of mailing of the international search report

06/08/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Vuillamy, V.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/NL2004/000271

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 94/13150 A (NABISCO INC) 23 June 1994 (1994-06-23) page 3, paragraph 3 - page 4, paragraph 3 page 5, paragraph 1 - page 6, paragraph 1 page 7, paragraph 3 - page 10, paragraph 1 claims examples	1-4
X	US 4 396 633 A (TRESSER DAVID) 2 August 1983 (1983-08-02) column 2, lines 46-63 column 4, lines 5-9 column 6, lines 1-9 example 1 column 12, lines 13-28	1-11
X	WO 94/16573 A (NABISCO INC) 4 August 1994 (1994-08-04) page 4, paragraph 4 - page 5, paragraph 1 page 11, paragraph 2 example 1	1-11
A	US 4 293 572 A (ASH DAVID J ET AL) 6 October 1981 (1981-10-06) column 6, line 25 - column 7, line 20 claims 1,2	10,11
A	DATABASE WPI Section Ch, Week 197636 Derwent Publications Ltd., London, GB; Class D13, AN 1976-68290X XP002290069 & SU 491 371 A (MOSC FATS RES INST) 4 March 1976 (1976-03-04) abstract	10,11
A	EP 0 509 566 A (UNILEVER NV ; UNILEVER PLC (GB)) 21 October 1992 (1992-10-21) the whole document	1-11

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/NL2004/000271

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9715198	A	01-05-1997	AU 7492696 A WO 9715198 A1	15-05-1997 01-05-1997
US 5662953	A	02-09-1997	US 5565232 A US 5456939 A US 5378490 A US 5258197 A AT 181210 T CA 2097800 A1 DE 69131354 D1 DE 69131354 T2 DK 560944 T3 EP 0560944 A1 ES 2136081 T3 GR 3031199 T3 JP 3504260 B2 JP 6506106 T US 5391383 A US 5434278 A US 5380544 A WO 9210105 A1 US 5411756 A US 5552174 A US 6022577 A US 5407695 A US 5362508 A US 5380538 A US 5374440 A AU 6509090 A CA 2042057 A1 EP 0445278 A1 JP 4501812 T WO 9103944 A1 US 5268192 A US 5240726 A AT 192902 T CA 2105577 A1 DE 69231067 D1 DE 69231067 T2 DK 724389 T3 EP 0724389 A1 ES 2149176 T3 GR 3034180 T3 WO 9215200 A1	15-10-1996 10-10-1995 03-01-1995 02-11-1993 15-07-1999 08-06-1992 22-07-1999 27-01-2000 10-01-2000 22-09-1993 16-11-1999 31-12-1999 08-03-2004 14-07-1994 21-02-1995 18-07-1995 10-01-1995 25-06-1992 02-05-1995 03-09-1996 08-02-2000 18-04-1995 08-11-1994 10-01-1995 20-12-1994 18-04-1991 21-03-1991 11-09-1991 02-04-1992 04-04-1991 07-12-1993 31-08-1993 15-06-2000 07-09-1992 21-06-2000 02-11-2000 14-08-2000 07-08-1996 01-11-2000 30-11-2000 17-09-1992
WO 9413150	A	23-06-1994	US 5380538 A AT 214548 T AU 689092 B2 AU 5871794 A BR 9307658 A CA 2151053 A1 DE 69331748 D1 DE 69331748 T2 EP 0674480 A1 ES 2173114 T3 FI 952963 A JP 3496075 B2 JP 8504582 T	10-01-1995 15-04-2002 26-03-1998 04-07-1994 08-09-1999 23-06-1994 25-04-2002 10-10-2002 04-10-1995 16-10-2002 13-07-1995 09-02-2004 21-05-1996

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/NL2004/000271

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9413150	A	NO 952373 A NZ 259788 A WO 9413150 A1	15-08-1995 25-06-1996 23-06-1994
US 4396633	A 02-08-1983	AT 6020 T AU 540544 B2 AU 6120980 A AU 540545 B2 AU 6121080 A DE 3061818 D1 DE 3066386 D1 DK 122381 A DK 122481 A EP 0023151 A1 EP 0023152 A1 WO 8100189 A1 WO 8100190 A1 GB 2068706 A ,B GB 2066646 A JP 56500833 T JP 56500873 T US 4394392 A AT 2378 T AT 2710 T AU 542017 B2 AU 6120680 A DE 3062282 D1 DK 122281 A EP 0023150 A1 WO 8100191 A1 JP 56500874 T US 4430350 A	15-02-1984 22-11-1984 13-02-1981 22-11-1984 13-02-1981 10-03-1983 08-03-1984 18-03-1981 18-03-1981 28-01-1981 28-01-1981 05-02-1981 05-02-1981 19-08-1981 15-07-1981 25-06-1981 02-07-1981 19-07-1983 15-02-1983 15-03-1983 31-01-1985 13-02-1981 14-04-1983 18-03-1981 28-01-1981 05-02-1981 02-07-1981 07-02-1984
WO 9416573	A 04-08-1994	US 5391383 A AU 671355 B2 AU 6094394 A BR 9405665 A CA 2153413 A1 EP 0680262 A1 FI 953535 A JP 3328743 B2 JP 8505779 T NO 952883 A NZ 261757 A WO 9416573 A1	21-02-1995 22-08-1996 15-08-1994 21-11-1995 04-08-1994 08-11-1995 21-07-1995 30-09-2002 25-06-1996 28-08-1995 27-08-1996 04-08-1994
US 4293572	A 06-10-1981	DE 2906803 A1 FI 790199 A FR 2417946 A1 GB 2015315 A JP 1108438 C JP 54132248 A JP 56045580 B NL 7901535 A NO 790117 A SE 7901779 A	06-09-1979 29-08-1979 21-09-1979 12-09-1979 13-08-1982 15-10-1979 27-10-1981 30-08-1979 29-08-1979 29-08-1979
SU 491371	A 15-11-1975	SU 491371 A1	15-11-1975

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/NL2004/000271

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0509566	A	21-10-1992	AT 114408 T	15-12-1994
			AU 645398 B2	13-01-1994
			AU 1148292 A	17-09-1992
			CA 2062540 A1	12-09-1992
			DE 69200736 D1	12-01-1995
			DE 69200736 T2	27-04-1995
			DK 509566 T3	01-05-1995
			EP 0509566 A1	21-10-1992
			ES 2066548 T3	01-03-1995
			JP 1964995 C	25-08-1995
			JP 5103581 A	27-04-1993
			JP 6104027 B	21-12-1994
			US 5405626 A	11-04-1995
			ZA 9201815 A	13-09-1993